
DPCF100 DPCMT100



	DRY POPPET COUPLINGS		
PART NO	DESCRIPTION	MAX PSI	QTY
DPCF100	FEMALE DRY POPPET COUPLER, 1" FEMALE NPT THREADS W/ FKM SEALS	100	1
DPCM100	MALE DRY POPPET ADAPTER, 1" FEMALE NPT THREADS W/ FKM SEALS	150	1
DPCMT100	MALE DRY POPPET ADAPTER, W/1" MALE THREADED BODY 2" FEMALE NPT THREADS W/ FKM SEALS	150	1

*Note: Male adapter and female coupler shown coupled together but sold separately.

DRY POPPET COUPLINGS

FEATURES

- Lightweight
- Minimal fluid spillage
- Easy to use
- Economical
- Reduces risk of exposure
- Wide range of chemical resistance
- Maximum operating temperature 150° F
- 30 GPM maximum flow
- Precision molded in polypropylene
- 1" female NPT threads

APPLICATIONS

- Agriculture
- Industrial
- Pharmaceutical
- Chemical processing



DRY-MATES

druckflexQuick-Couplings for Tubes and Hoses

11/2" POLY DRY-MATES


FEATURES

- Lightweight
- Easy to use
- Economical
- · Reduces risk of exposure
- Wide range of chemical resistance
- Unrestricted 1½" flow
- Patented double ball design with cam lever connection
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 1½" = 2ml



REPAIR KIT INCLUDES:


- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring




FIBERGLASS REINFORCED POLYPROPYLENE

	1½" POLY MALE DRY-MATE					
PART NO	PART NO DESCRIPTION		PIPE SIZE	OPENING THRU BALL	QTY	
DM150A	1½" MALE X FPT NPT W/FKM SEALS	100	1½"	11/2"	1	
DM150AE	1½" MALE X FPT NPT W/EPDM SEALS 100 1½" 1½"		1			
DM150AT	T 1½" MALE X FPT NPT W/ KALREZ® SEALS 100 1½" 1½"		11/2"	1		
DM150AB	1½" MALE X FPT BSP W/FKM SEALS	100	11/2"	11/2"	1	
DM150ABE	1½" MALE X FPT BSP W/EPDM SEALS	100	11/2"	11/2"	1	
DM150ABT	1½" MALE X FPT BSP W/ KALREZ® SEALS	100	11/2"	11/2"	1	

	1½" POLY FEMALE D	RY-MA	ATE		
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
DM150D	1½" FEMALE X FPT NPT W/FKM SEALS	100	1½"	11/2"	1
DM150DE	1½" FEMALE NPT W/EPDM SEALS	100	1½"	11/2"	1
DM150DT	1½" FEMALE NPT W/KALREZ® SEALS	100	1½"	11/2"	1
DM150DB	1½" FEMALE X FPT BSP W/FKM SEALS	100	1½"	11/2"	1
DM150DBE	1½" FEMALE X FPT BSP W/EPDM SEALS	100	1½"	11/2"	1
DM150DBT	1½" FEMALE X FPT BSP W/ KALREZ® SEALS	100	1½"	1½"	1



	REPLAC	EMENT PARTS MALE	
ITEM	PART NO	DESCRIPTION	QTY
1	DM20153M	MALE HANDLE	1
1	DB20153M	LOW PROFILE HANDLE	1
2	DB20290	FKM FACE SEAL	1
2	DM20295A	EPDM FACE SEAL	1
2	DM20296	KALREZ® FACE SEAL	1
3	DM200CAP	DUST CAP	1
KIT	DM20200A	REPAIR KIT FOR DM150A	1



	REPLACE	EMENT PARTS FEMALE	
ITEM	PART NO	DESCRIPTION	QTY
1	DM20294A	FKM FACE SEAL	1
1	DM20295A	EPDM FACE SEAL	1
1	DM20296	KALREZ® FACE SEAL	1
2	DM20153F	FEMALE HANDLE	1
3	DM200PL	DUST PLUG	1
KIT	DM20200D	REPAIR KIT FOR DM150D	1






FIBERGLASS REINFORCED POLYPROPYLENE

	2" POLY MALE DRY-MATE					
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	
DM200A	2" MALE X FPT NPT W/FKM SEALS	100	2"	1½"	1	
DM200AB	2" MALE X FPT BSP W/FKM SEALS	100	2"	1½"	1	
DM200AE	2" MALE X FPT NPT W/EPDM SEALS	100	2"	1½"	1	
DM200AT	2" MALE X FPT NPT W/ KALREZ® SEALS	100	2"	1½"	1	
DMMT201A	2" MALE X MALE NPT W/LOW PROFILE HANDLE	100	2"	1½"	1	
DMMT201AE	2" MALE X MALE NPT W/LOW PROFILE HANDLE W/EDPM SEALS	100	2"	1½"	1	

2" POLY FEMALE DRY-MATE					
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
DM200D	2" FEMALE X FPT NPT W/FKM SEALS	100	2"	11/2"	1
DM200DB	2" FEMALE X FPT BSP W/FKM SEALS	2" FEMALE X FPT BSP W/FKM SEALS 100 2" 1½"		1	
DM200DE	2" FEMALE W/EPDM SEALS	100	2"	11/2"	1
DM200DT	2" FEMALE W/KALREZ® SEALS	100	2"	11/2"	1



	REPLAC	CEMENT PARTS MALE	
ITEM	PART NO	DESCRIPTION	QTY
1	DM20153M	MALE HANDLE	1
1	DB20153M	LOW PROFILE HANDLE	1
2	DB20290	FKM FACE SEAL	1
2	DM20295A	EPDM FACE SEAL	1
2	DM20296	KALREZ® FACE SEAL	1
3	DM200CAP	DUST CAP	1
KIT	DM20200A	REPAIR KIT FOR DM200A	1

ITEM	PART NO	DESCRIPTION	QTY
1	DM20294A	FKM FACE SEAL	1
1	DM20295A	EPDM FACE SEAL	1
1	DM20296	KALREZ® FACE SEAL	1
2	DM20153F	FEMALE HANDLE	1
3	DM200PL	DUST PLUG	1
KIT	DM20200D	REPAIR KIT FOR DM200D	1

2" POLY DRY-MATES

FEATURES

- Lightweight
- Easy to use
- Economical
- Reduces risk of exposure
- Wide range of chemical resistance
- Unrestricted 1½" flow
- Patented double ball design with cam lever connection
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 2" = 2.6ml



- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring



2" FULL PORT POLY DRY-MATES

FEATURES


- Lightweight
- Easy to use
- Economical
- Reduces risk of exposure
- Wide range of chemical resistance
- Unrestricted 2" flow
- Patented double ball design with cam lever connection
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 2" FP = 3.6ml



DM220D DM220A

2" FULL PORT POLY DRY-MATES					
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
DM220D	2" FEMALE X FPT NPT W/FKM SEALS	225	2"	2"	1
DM220DB	2" FEMALE BSP X FPT NPT W/FKM SEALS	225	2"	2"	1
DM220A	2" MALE X FPT W/FKM SEALS	225	2"	2"	1
DM220AB	2" MALE BSP X FPT W/FKM SEALS	225	2"	2"	1

- Body gasket
- Thrust washer
- Ball seats
- · Upper stem bushing
- Stem o-ring
- Face seal



	REPLAC	CEMENT PARTS MALE	
ITEM	PART NO	DESCRIPTION	QTY
1	DM25153M	MALE HANDLE	1
2	DM220CAP	DUST CAP	1
KIT	DM25200	REPAIR KIT	1

	REPLACE	EMENT PARTS FEMALE	
ITEM	PART NO	DESCRIPTION	QTY
1	DM25153F	FEMALE HANDLE	1
2	DM221PL	DUST PLUG	1
KIT	DM25200	REPAIR KIT	1





DM300AFP

3" FULL PORT POLY DRY-MATES					
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
DM300AFP	3" FP MALE X 3" FEMALE NPT THREADS W/ FKM SEALS	150	3"	3"	1
DM300ABFP	3" FP MALE X 3" BSP THREADS W/ FKM SEALS	150	3"	3"	1
DM300DFP	3" FP FEMALE X 3" FEMALE NPT THREADS W/ FKM SEALS	150	3"	3"	1
DM300DBFP	3" FP FEMALE X 3" BSP THREADS W/ FKM SEALS	150	3"	3"	1


3" FULL PORT POLY DRY-MATES

FEATURES


- Lightweight
- Easy to use
- Economical
- · Reduces risk of exposure
- Wide range of chemical resistance
- Unrestricted 3" flow
- Patented double ball design with cam lever connection
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 3" = 20ml



- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring
- Face seal







	REPLACE	MENT PARTS FEMALE	
ITEM	PART NO	DESCRIPTION	QTY
1	DM35294	FACE SEAL FKM	1
2	DM35153F	FEMALE HANDLE	1
3	DM300PL	DUST PLUG	1
KIT	DM35200	REPAIR KIT	1

DRY-MATES

CRUCKFIEXQuick-Couplings for Tubes and Hoses

1" FULL PORT STAINLESS STEEL DRY-MATES

FEATURES


- 316 stainless steel construction
- Unrestricted 1" flow
- Patented double ball design with cam lever connection
- 300°F maximum operating temperature
- 100% PTFE ball seats
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 1" FP = 1.7ml



- Ball
- Body gasket
- Thrust washer
- Ball seats
- · Upper stem bushing
- Stem o-ring
- Face seal



1" FULL PORT STAINLESS STEEL DRY-MATE					
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
DM100ASS	1" MALE X FPT NPT W/ PTFE SEALS	150	1"	1"	1
DM100ABSS	1" MALE X FPT BSP W/ PTFE SEALS	150	1"	1"	1
DM100DSS	1" FEMALE X FPT NPT W/ FKM SEALS	150	1"	1"	1
DM100DSSE	1" FEMALE X FPT NPT W/ EPDM SEALS	150	1"	1"	1
DM100DSST	1" FEMALE X FPT NPT W/ KALREZ®SEALS	150	1"	1"	1
DM100DBSS	1" FEMALE X FPT BSP W/ FKM SEALS	150	1"	1"	1
DM100DBSSE	1" FEMALE X FPT BSP W/ EPDM SEALS	150	1"	1"	1
DM100DBSST	1" FEMALE X FPT BSP W/ KALREZ®SEALS	150	1"	1"	1



	REPLACEMENT PARTS MALE				
ITEM	PART NO	DESCRIPTION	QTY		
1	DM100CAP	DUST CAP	1		
KIT	DM101SS	REPAIR KIT	1		

	REPLACE	EMENT PARTS FEMALE	
ITEM	PART NO	DESCRIPTION	QTY
1	DM10294A	FKM FACE SEAL	1
1	DM10295A	EPDM FACE SEAL	1
1	DM10296	KALREZ® FACE SEAL	1
2	DM100PL	POLY PLUG	1
KIT	DM102SSV	FKM REPAIR KIT	1
KIT	DM102SSE	EPDM REPAIR KIT	1
KIT	DM102SST	KALREZ® REPAIR KIT	1






DM150ASS

DM150DSS

1½" FULL PORT STAINLESS STEEL DRY-MATE						
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY	
DM150ASS	1½" MALE X FPT NPT W/ PTFE SEALS	150	1½"	11/2"	1	
DM150ABSS	1½" MALE X FPT BSP W/ PTFE SEALS	150	1½"	11/2"	1	
DM150DSS	1½" FEMALE X FPT NPT W/ FKM SEALS	150	1½"	11/2"	1	
DM150DSSE	1½" FEMALE X FPT NPT W/ EPDM SEALS	150	1½"	11/2"	1	
DM150DSST	11/2" FEMALE X FPT NPT W/ KALREZ® SEALS	150	1½"	11/2"	1	
DM150DBSS	1½" FEMALE X FPT BSP W/ FKM SEALS	150	1½"	11/2"	1	
DM150DBSSE	1½" FEMALE X FPT BSP W/ EPDM SEALS	150	1½"	11/2"	1	



	REPLACEMENT PARTS MALE				
ITEM	PART NO	DESCRIPTION	QTY		
1	DM200ACAP	DUST CAP	1		
KIT	DM201SS	REPAIR KIT	1		

	REPLACEMENT PARTS FEMALE				
ITEM	PART NO	DESCRIPTION	QTY		
1	DM20294A	FKM FACE SEAL	1		
1	DM20295A	EPDM FACE SEAL	1		
1	DM20296	KALREZ® FACE SEAL	1		
2	DM200APL	DUST PLUG	1		
KIT	DM202SSV	FKM REPAIR KIT	1		
KIT	DM202SSE	EPDM REPAIR KIT	1		
KIT	DM202SST	KALREZ® REPAIR KIT	1		

11/2" FULL PORT STAINLESS STEEL DRY-MATES

FEATURES

- 316 stainless steel construction
- Unrestricted 1½" flow
- Patented double ball design with cam lever connection
- 300°F maximum operating temperature
- 100% PTFE ball seats
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 1½" FP = 3ml



- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring
- Face seal



2" STAINLESS STEEL **DRY-MATES**

FEATURES

- 316 stainless steel construction
- Patented double ball design with cam lever connection
- 300°F maximum operating temperature
- 100% PTFE ball seats
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 2" = 3.6ml








2 STANDARD PORT STAINLESS STEEL DRI-MATE					
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
DM200ASS	2" MALE X FPT NPT W/ PTFE SEALS	150	2"	11/2"	1
DM200ABSS	2" MALE X FPT BSP W/ PTFE SEALS	150	2"	11/2"	1
DM200DSS	2" FEMALE X FPT NPT W/ FKM SEALS	150	2"	11/2"	1
DM200DSSE	2" FEMALE X FPT NPT W/ EPDM SEALS	150	2"	11/2"	1
DM200DSST	2" FEMALE X FPT NPT W/ KALREZ® SEALS	150	2"	11/2"	1
DM200DBSS	2" FEMALE X FPT BSP W/ FKM SEALS	150	2"	11/2"	1
DM200DBSSE	2" FEMALE X FPT BSP W/ EPDM SEALS	150	2"	1½"	1
DM200DBSST	2" FEMALE X FPT BSP W/ KALREZ® SEALS	150	2"	11/2"	1



- Ball
- Body gasket
- Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring
- Face seal



REPLACEMENT PARTS MALE				
ITEM	PART NO	DESCRIPTION	QTY	
1	DM200ACAP	DUST CAP	1	
KIT	DM201SS	REPAIR KIT	1	



REPLACEMENT PARTS FEMALE				
ITEM	PART NO	DESCRIPTION	QTY	
1	DM20294A	FKM FACE SEAL	1	
1	DM20295A	EPDM FACE SEAL	1	
1	DM20296	KALREZ® FACE SEAL	1	
2	DM200APL	POLY PLUG	1	
KIT	DM202SSV	FKM REPAIR KIT	1	
KIT	DM202SSE	EPDM REPAIR KIT	1	
KIT	DM202SST	KALREZ® REPAIR KIT	1	



2" FULL PORT STAINLESS STEEL DRY-MATES

FEATURES

- 316 stainless steel construction
- Unrestricted 2" flow
- Patented double ball design with cam lever connection
- 300°F maximum operating temperature
- 100% PTFE ball seats
- When properly installed and operated, the assembly will not accidentally separate while fluid is flowing; preventing costly mishaps
- Spillage data: 2" FP = 3.8ml




DM220ASS

DM220DSS


2" FULL PORT STAINLESS STEEL DRY-MATE					
PART NO	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	QTY
DM220ASS	2" FULL PORT MALE X FPT NPT W/ PTFE SEALS	300	2"	2"	1
DM220ABSS	2" FULL PORT MALE X FPT BSP W/ PTFE SEALS	300	2"	2"	1
DM220DSS	2" FULL PORT FEMALE X FPT NPT W/ FKM SEALS	300	2"	2"	1
DM220DSSE	2" FULL PORT FEMALE X FPT NPT W/ EPDM SEALS	300	2"	2"	1
DM220DSST	2" FULL PORT FEMALE X FPT NPT W/ KALREZ® SEALS	300	2"	2"	1
DM220DBSS	2" FULL PORT FEMALE X FPT BSP W/ FKM SEALS	300	2"	2"	1



- Body gasket
 - Thrust washer
- Ball seats
- Upper stem bushing
- Stem o-ring







REPLACEMENT PARTS FEMALE			
ITEM	PART NO	DESCRIPTION	QTY
1	DM25294	FKM FACE SEAL	1
1	DM25294E	EPDM FACE SEAL	1
1	DM25294T	KALREZ® FACE SEAL	1
2	DM220PL	DUST PLUG	1
KIT	DM222SS	REPAIR KIT	1